

# Ultra 5500

## Matt Economic Paint

- Washable



### Description

A Standard quality Paint on acrylic copolymer emulsion.

### Features

Durable matt finish washable with Water and mild detergent. Non yellowing on aging.

### Uses

On interior drywalls plaster and concrete Surfaces.

### Technical Data

- Color : White, (other colors on request)
- Appearance : Matt
- Theoretical spreading rate : 9.0 – 11.0 sq .m. / Lit per coat, on Film thickness : 30-40 microns (one coat dry) Drying time at 25 c and 60% relative humidity  
Dust free : 30-40 minutes  
Tack free : 1-2 hours  
Recoat ability : 8 hours

### Application information

Recommended thinner : Tap water

Surface preparation : Surface should be clean and dry. Wash With warm Soap, water, and then rinse With fresh water.

	Thinning	Thinner	Nozzle	Pressure
Spray	5 - 10%	Water	0.3-0.4	3-4
Brush or roller	5 - 10%	Water	---	---

# Ultra 5500

## Matt Economic Paint

### ■ Washable



#### Recommended system

- Concrete, cementous, plaster and masonry
- One coat sealer clear, or sealer white ( Sealer Strong 1100 )
- One -Two coat putty plasma 2200 according to surface condition sand with sanding paper between successive coats
- Two – three coat Ultra Matt Paint 5500
- Wood - One coat Wood undercoat or
- two – three coat Plasma Matt Paint Previously painted surfaces should be dulled by sanding then treated as new surface.

#### Application method

Brush, roller or conventional spray

#### Application Remarks

- Stir the container thoroughly before use periodically during use.
- Not to be applied at temperature below 5°C

#### Storage Information

SHELF LIFE : 18 months as well ventilated storage area, a way of direct sun.  
Net weight : Printed on plastic containers.

#### Safety Information

- Do not take internally
- Close container after each use
- Use with adequate ventilation (KEEP OUT REACH OF CHILDREN)

■ The information provided about the product is the result of our own laboratory and practical experience. Since the product is often used under different conditions. We cannot guarantee anything but the quality of the product itself. For more inquiries, please contact the technical office