

# ECO 4400

## ■ Matt Paint



### Description

An economic quality emulsion paint Based on acrylic copolymer emulsion  
Special Features : A Durable matt finish with good flow and Attractive appearance.

Suggested Uses : On interior drywalls, plaster and concrete Surface. As well as primed wooden surface.

### Technical Data

- Color: White
- Appearance : Matt
- Theoretical spreading Rate : 9-11 sq .m. / Lit per coat, on Ideal surface conditions.
- Film thickness : 35-40 microns (one coat dry)
- Drying time : at 25 °c and 60% relative humidity
- Superficial dryness time : 10-15 Minutes -Tack free : 3-4 hours
- Recoat ability : 18 hours

### Application Information

Recommended Thinner : Tap Water

Surface preparation : Surface should be clean and dry.

Wash with wet towel.

Recommend system

(Concrete, cementous: , plaster ,masonry :)

- one coat clear sealer Clear or sealer white (Sealer Strong 1100)
- One or two coats putty Plasma2200 depending on surface condition .sand between coat

- two - three coat Eco 4400

wood:

- One coat primer ( Synthetic Matt )
- Two -three coat Eco4400
- Previously painted surfaces should be dulled by sanding, then treated as new surface.

# ECO 4400

## ■ Matt Paint



	Thinning	Thinner	Nozzle	Pressure
Spray	10-15 %	Water	0.3-0.4	3-4
Brush or roller	5-10 %	Water	---	---

### Application method

Brush , roller or conventional spray

### Application Remarks

- stir container thoroughly before use And periodically during use .
- Do not apply when temperature is below 5 °c

### STORAGE INFORMATION

SHELF LIFE : 18 month as well ventilated storage area, a way of direct sun.  
Weight : Printed on Can

### Safety Information

- Do not take internally
  - Close container after each use
- (KEEP OUT OF REACH OF CHILDREN)

■ The information provided about the product is the result of our own laboratory and practical experience. Since the product is often used under different conditions. We cannot guarantee anything but the quality of the product itself. For more inquiries, please contact the technical office